

# RAPID / Caratteristiche Tecniche

Modello	RA015	RA024	RA032	RA035	RA043	RA054
Omologazione CE	0694BN4077	0694BN4077	0694BN4077	0694BN4077	0694BN4077	0694BN4077
Potenza Termica kW	16,5	26,5	34,8	38,7	47,5	58,0
Portata Termica kW	15,3	24,3	31,7	34,9	43,6	53,4
Rendimento %	92,6	91,8	91,2	90,2	91,8	92,1
Consumo Gas (G20) (15°C-1013 mbar) (m³/h)	1,75	2,8	3,68	4,1	5,03	6,14
Consumo Gas (G30/G31) (15°C-1013 mbar) (m³/h)	1,06	1,71	2,24	2,49	3,06	3,73
Consumo Gas (G2.350) (15°C-1013 mbar) (m³/h)	2,44	3,93	5,16	5,73	7,04	8,59
Ø Tubi aspirazione/scarico	80/80	80/80	80/80	80/80	80/80	80/80
Press. Disponibile scarico fumi	50	50	90	90	110	110
Portata Aria (T 15°C) m³/h	1.600	3.050	3.050	3.800	5.000	6.250
Gittata (**) m	22	22	24	25	30	32
Δ T Aria °C	27,4	22,9	29,8	26,3	25,0	24,5
Velocità ventilatori rpm	1.050	1.270	1.270	1.350	1.270	1.350
N° e Ø Ventilatore mm/°	1x350/25°	1x400/22°	1x400/22°	1x420/27°	2x400/22°	2x420/27°
Tensione di alimentazione V/Hz	230/50	230/50	230/50	230/50	230/50	230/50
Potenza elettrica assorbita W	220	260	260	330	500	620
Press. Sonora in campo libero 6m dB(A)	39,9	44,4	44,4	47,5	47,4	50,5

# RAPID / Dimensioni

Modello	Dimensioni				Bocchette			Mensole			Alimentazione Gas			Peso Kg
	L	B	H	V	HB	LB	IM	IS	ID	DM	GAS	GO	GV	
RA015	720	640	650	140	530	415	450	116	174	475	3/4"	186	263	70
RA024	900	640	650	140	530	595	450	206	264	475	3/4"	186	263	80
RA032	900	640	650	140	530	595	450	206	264	475	3/4"	186	263	84
RA035	900	640	650	140	530	595	450	206	264	475	3/4"	186	263	90
RA043	1240	640	650	140	530	935	780	228	252	475	3/4"	186	263	112
RA054	1240	640	740	140	620	935	780	228	252	475	3/4"	183	352	117

